Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1AV1106A **SIMOTICS GP - 100 L - IM B14 - 2p**

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project
Remarks		

Safe Area

-/-

Electrical data

U [V]	Δ / Y	f [Hz]	P [kW]	P [hp]	I [A]	n [1/min]	M [Nm]	η 3) 4/4	η 3) 3/4	η 3) 2/4	cosφ 3) 4/4	cosφ 3) 3/4	cosφ 3) 2/4	I_A/I_N I_I/I_N	M_A/M_N T_I/T_N	M_K/M_N T_B/T_N	IE-CL
DOL duty (S1) - 155(F) to 130(B)																	
230	Δ	50	4.00	-/-	14.20	2850	13.4	83.1	83.9	83.0	0.85	0.79	0.67	7.0	4.5	4.1	IE1
400	Y	50	4.00	-/-	8.20	2850	13.4	83.1	83.9	83.0	0.85	0.79	0.67	7.0	4.5	4.1	IE1
460	Y	60	4.60	-/-	7.90	3450	12.7	84.5	85.0	83.9	0.86	0.81	0.71	7.5	4.0	3.9	IE1

IM B14 / IM 3601		FS 100 L		IP55	UKCA	IEC/EN 60034	IEC, DIN, ISO, VDE, EN			

Environmental conditions : -20 °C - +40 °C / 1000 m

Locked rotor time (hot / cold) : 5.3 s | 9.5 s

Mechanical data

Sound level (SPL / SWL) at 50Hz|60Hz	67 / 79 dB(A) 2) 3)	71 / 83 dB(A) 2) 3)	Vibration severity grade	A
Moment of inertia	0.0044 kg m²		Thermal class	F
Bearing DE | NDE	6206 2Z C3	6206 2Z C3	Duty type	S1
bearing lifetime			Direction of rotation	bidirectional
L_{10mh} $F_{Rad\ min}$ for coupling operation 50|60Hz 1)	40000 h	32000 h	Frame material	aluminum
Regreasing device	Without		Net weight of the motor (IM B3)	25 kg
Grease nipple	-/-		Coating (paint finish)	Standard paint finish C2
Type of bearing	Preloaded bearing DE		Color, paint shade	RAL7030
Condensate drainage holes	Without		Motor protection	(A) without (Standard)
External earthing terminal	Without		Method of cooling	IC411 - self ventilated, surface cooled

Terminal box

Terminal box position	top	Max. cross-sectional area	4 mm²
Material of terminal box	Aluminium	Cable diameter from ... to ...	11 mm - 21 mm
Type of terminal box	TB1 F00	Cable entry	2xM32x1,5
Contact screw thread	M4	Cable gland	2 plugs

Notes:

I_A/I_N = locked rotor current / current nominal
M_A/M_N = locked rotor torque / torque nominal
M_K/M_N = break down torque / nominal torque

1) L10mh according to DIN ISO 281 10/2010
2) at rated power / at full load
3) Value is valid only for DOL operation with motor design IC411

responsible dep.	technical reference	created by	approved by	
IN LVM		SPC		

Technical data are subject to change! There may be discrepancies between calculated and rating plate values.

Link documents

SIEMENS

document type	document status
datasheet	released
title	document number
1LE1002-1AA62-2KA4	

rev.	creation date	language	Page
950	2023-10-04	en	1/1

© INNOMOTICS 2023