
SAF Crimping Ferrule VHP TP-F

An extreme performing hose needs extreme performing fittings.
For a hose of this Very High Pressure capability the ferrule and insert need to be specifically designed.

Transfer Oil strongly recommend the use of original parts.
For new applications, ferrules or fittings not listed in this file please contact us.

WARNING!
Always check bore collapse using go/no go bore gauge.
If needed adjust crimping diameter in order to obtain the optimal bore collapse.



Carbon STEEL	AISI 316L STEEL	Description	Minimum Pack quantity	Hoze Size		C	D	L
Part. No	Part. No			DN	inch	mm	mm	mm
SAF101	SAF801	1/8" FERRULE VHP TP-F	20 pcs	4	1/8"	13,5	9,8	24
SAF111	SAF811	3/16" FERRULE VHP TP-F	20 pcs	5	3/16"	15,5	11,8	29
SAF121	SAF821	1/4" FERRULE VHP TP-F	20 pcs	6	1/4"	20	15	38,4
SAF131	SAF831	5/16" FERRULE VHP TP-F	20 pcs	8	5/16"	24	18,2	41
SAF141	SAF841	3/8" FERRULE VHP TP-F	20 pcs	10	3/8"	26	20	44
SAF151	SAF851	1/2" FERRULE VHP TP-F	20 pcs	12	1/2"	33	25,5	54
SAF161	SAF861	5/8" FERRULE VHP TP-F	2 pcs	16	5/8"	36,5	28,7	53
SAF171	SAF871	3/4" FERRULE VHP TP-F	2 pcs	20	3/4"	40	32	60
SAF172	SAF872	3/4" FERRULE VHP TP-F	2 pcs	20	3/4"	39	31	60
SAF181	SAF881	1" FERRULE VHP TP-F	2 pcs	25	1"	50,8	41,5	63

Ferrule selection by hose family

All ferrules are available both with standard and AISI 316L steel

	AISI 316L STEEL	SAF801	SAF811	SAF821	SAF831	SAF841	SAF851	SAF861	SAF871	SAF872	SAF881
	CARBON STEEL	SAF101	SAF111	SAF121	SAF131	SAF141	SAF151	SAF161	SAF171	SAF172	SAF181
		1/8"	3/16"	1/4"	5/16"	3/8"	1/2"	5/8"	3/4"	3/4"	1"
HYDRAULIC											
041X VHP 10000				•		•					
046X VHP NON COND		•	•	•		•					
040X VHP 10000 MARINER				•		•	•				
080X VHP EXTRA				•							
060X OFF SHORE MASTER 5000			•	•		•	•		•		•
168X OFF SHORE MASTER 10000				•							
INDUSTRIAL											
159X CNG 5000 COMP. NATURAL GAS HOSE				•		•	•			•	
049X HP AGGRESSIVE CHEMICALS						•	•				
048X VHP 10000 AGG. CHEMICALS				•	•	•	•	•	•		•