Hypress EASY K 2SC
TFA202K

APPLICATIONS:





APPLICABLE SPECS. :

EN 857 2SC - ISO 11237

Compact hose according to EN 857 - ISO 11237. No skive solution. Smooth cover.

Internal hose: Synthetic rubber, extruded whole without joints, of uniform thickness.

Reinforcement: 2 high tensile steel wire braids.

Covering: Synthetic rubber resistant to oils, fuels and atmospheric conditions.

Recommended fluid: Mineral and biological oils, glicol-water based, water, lubricants.

Operating temperature: from -40 to +100°C, from -40 to +70° C for water based fluids, from 0 to +70°C water.

Part number	ID		Size	OD	Max WP		Min BP		Min BR		Weight		Ferrule
	in	mm		mm	bar	psi	bar	psi	mm	inch	kg/m	lb/ft	
TFA202K-04	1/4″	6.4	4	13.3	400	5800	1600	23200	75	2.953	0.281	0.189	001C-04
TFA202K-05	5/16″	8.0	5	14.8	350	5075	1400	20300	85	3.346	0.327	0.220	001C-05
TFA202K-06	3/8″	9.5	6	17.1	330	4785	1320	19140	90	3.543	0.418	0.281	001C-06
TFA202K-08	1/2″	12.7	8	20.0	275	3988	1100	15950	130	5.118	0.525	0.353	001C-08
TFA202K-10	5/8″	16.0	10	23.2	250	3625	1000	14500	170	6.693	0.627	0.421	001C-10
TFA202K-12	3/4″	19.0	12	27.6	215	3118	860	12470	200	7.874	0.782	0.526	001C-12
TFA202K-16	1 ″	25.4	16	35.8	165	2393	660	9570	250	9.843	1.176	0.790	001C-16

MARKING: Mylar version

