Hypress EASY K 2SC

TFA202KI



APPLICATIONS :

APPLICABLE SPECIFICATIONS

EN 857 2SC - ISO 11237

Compact hose according to EN 857 ISO 11237. NO-SKIVE solution. Smooth cover.

Inner tube: Synthetic rubber, extruded whole without joints, of uniform thickness.
Reinforcement: 2 high tensile steel wire braids.
Coverage: Smooth synthetic rubber, resistant to oils, fuels and atmospheric conditions.
Recommended fluids: Mineral and biological oils, glicol-water based, water, lubricants.
working temperature: from -40 to +100°C, from -40 to +70° C for water based fluids, from 0 to +70°C water.

Product number	ID		Dimension	OD	Max WP		Min BP		Min BR		Weight (approx)		Ferrule
	in	mm	dash size		bar	psi	bar	psi	mm	inch	kg/m	lb/ft	
TFA202KI04	1/4"	6.4	04	13.3	400	5800	1600	23200	75	2.953	0.281	0.189	001C-04
TFA202KI05	5/16"	8	05	14.8	350	5075	1400	20300	85	3.346	0.327	0.22	001C-05
TFA202KI06	3/8"	9.5	06	17.1	330	4785	1320	19140	90	3.543	0.418	0.281	001C-06
TFA202KI08	1/2"	12.7	08	20	275	3988	1100	15950	130	5.118	0.525	0.353	001C-08
TFA202KI10	5/8"	16	10	23.2	250	3625	1000	14500	170	6.693	0.627	0.421	001C-10
TFA202KI12	3/4"	19	12	27.6	215	3118	860	12470	200	7.874	0.782	0.526	001C-12
TFA202KI16	1 "	25.4	16	35.8	165	2393	660	9570	250	9.843	1.176	0.79	001C-16

Marking: Ink-jet