INTERPUMP HySO-FLEX 5K WS

TIS0035



APPLICATIONS :



APPLICABLE SPECIFICATIONS

Exceeds ISO 18752/CC - SAE 100R13

High Flexibility and Half Bend Radius. Qualification according ISO 18752/CC.

Inner tube: Synthetic rubber, extruded whole without joints, of uniform thickness.
Reinforcement: 4 steel wire spirals.
Coverage: Anti-abrasive synthetic rubber, resistant to oils, fuels and atmospheric conditions.
Recommended fluids: Mineral and biological oils, water, water based fluid, lubricants.
working temperature: from -40 to +120°C from -40 to +70° C for water based fluids, from 0 to +70°C water.

Product number	ID		Dimension	OD	Max WP		Min BP		Min BR		Weight (approx)		FERRULE		One piece
	mm	in	dash size		bar	psi	bar	psi	mm	inch	lb/ft	kg/m	TWO PIECES NO SKIVE	TWO PIECES SKIVE	Fitting series
TIS0035-06	9.5	3/8"	06	19.7	350	5075	1400	20300	65	2.559	0.417	0.620	0NI4-06	0SI4-06	N series
TIS0035-08	12.7	1/2 "	08	22.5	350	5075	1400	20300	90	3.543	0.485	0.722	0NI4-08	0SI4-08	N series
TIS0035-10	15.9	5/8"	10	26.2	350	5075	1400	20300	100	3.937	0.630	0.938	0NI4-10	0SI4-10	N series
TIS0035-12	19	3/4"	12	29.7	350	5075	1400	20300	120	4.724	0.758	1.129	0NI4-12	0009-12	N series
TIS0035-16	25.4	1"	16	36.7	350	5075	1400	20300	150	5.906	1.090	1.622	0NI4-16	004N-16	N series
TIS0035-20	31.8	1.1/4"	20	45.0	350	5075	1400	20300	210	8.268	1.644	2.446	0NI4-20	004N-20	N series
TIS0035-24	38	1.1/2"	24	52.9	350	5075	1400	20300	250	9.843	2.211	3.291	0NI4-24	004N-24	N series

Available with MSHA and Mega cover. In case of order use code TISM035 and TISV035.