SABBIA/SP6C/PA



IT IMPIEGO

Tubo in gomma spiralato ondulato idoneo per aspirazione e mandata in impieghi gravosi di sabbia, vetro, ceramica o graniglia metallica.

• **TEMPERATURA:** -40°C +70°C

STRUTTURA

- **Sottostrato**: liscio in para beige resistente all'abrasione
- **Rinforzi**: tessuti sintetici ad alta resistenza, spirale metallica e cordicella di rame.
- **Copertura**: in gomma nera NR/SBR resistente all'abrasione e agli agenti atmosferici.
- **Superficie**: ondulata.
- **Marcatura**: listino arancio scritta nera "H.T. - BULK MATERIAL - S/D".

EN APPLICATION

Long lasting heavy duty **hardwall corrugated Cover rubber hose** suitable for suction and delivery of sand, glass, ceramics and cast steel shot.

• **TEMPERATURE RANGE:** -40°C +70°C

CONSTRUCTION

- **Tube**: beige, smooth, abrasion resistant para rubber.
- **Reinforcement**: high strength synthetic textile plies, helix wire and copper wire.
- **Cover**: black, abrasion and weathering resistant antistatic NR/SBR rubber.
- **Surface**: corrugated fabric finished.
- **Branding**: orange transfer tape black lettering "H.T. - BULK MATERIAL - S/D".

DIAMETRO INTERNO INSIDE DIAMETER		PESO TEORICO WEIGHT		PRESS. ESERCIZIO WORKING PRESSURE		PRESSIONE SCOPPIO BURST PRESSURE		ASPIRAZ. VACUUM	RAGGIO CURVATURA BENDING RADIUS		LUNGHEZZA LENGTH	
mm	inch	kg/mt	lbs/ft	bar	psi	bar	psi	bar	mm	inch	mt	ft
51	2"	1,35	0,91	6	90	18	270	0,9	75	2,95	20/40	65.5/131
76	3"	2,00	1.35"	6	90	18	270	0,9	110	4.33"	20/40	65.5/131
102	4"	3,20	2.16"	6	90	18	270	0,9	150	5.90"	20/40	65.5/131
127	5"	4,40	2,95	6	90	18	270	0,9	190	7.48"	20	65.5
152	6"	5,40	3,62	6	90	18	270	0,9	230	9.06"	20	65.5

Altri diametri e/o pressioni realizzabili su richiesta - Le caratteristiche e i dati tecnici possono essere modificati senza preavviso.

Other diameters and/or pressures are feasible upon request - The characteristics and technical data could be changed without warning.