INTERPUMP MARATHON 2SC

APPLICATIONS :



THE2M2K



APPLICABLE SPECIFICATIONS

IMM - exceed EN 857 2SC - ISO 11237 2SC

NO-SKIVE hose. Exceed EN specification. Impulse tested up to 1.000.000 cycles.

Inner tube: Synthetic rubber, extruded whole without joints, of uniform thickness.
Reinforcement: 2 high tensile steel wire braids.
Coverage: Smooth synthetic rubber, resistant to oils, fuelsa and atmospheric conditions.
Recommended fluids: Mineral and biological oils, glicol-water based, water, lubricants.
working temperature: from -40 to +120°C (intermittent 135°C), from -40 to +70° C for water based fluids, from 0 to +70°C water.

Product number	ID		Dimension	OD	Max WP		Min BP		Min BR		Weight (approx)		Ferrule
	in	mm	dash size		bar	psi	bar	psi	mm	inch	kg/m	lb/ft	
THE2M2K-04	1/4"	6.4	04	13.3	450	6525	1800	26100	50	1.969	0.285	0.192	001C-04
THE2M2K-05	5/16"	8	05	14.8	420	6090	1680	24360	60	2.362	0.33	0.222	001C-05
THE2M2K-06	3/8"	9.5	06	17.1	385	5582	1540	22330	70	2.756	0.422	0.284	001C-06
THE2M2K-08	1/2"	12.7	08	20.4	350	5075	1500	21750	80	3.15	0.566	0.349	001C-08
THE2M2K-10	5/8"	16	10	23.5	350	5075	1400	20300	90	3.543	0.665	0.447	001C-10
THE2M2K-12	3/4"	19	12	27.6	280	4060	1120	16240	120	4.725	0.865	0.531	001C-12
THE2M2K-16	1"	25.4	16	36	250	3625	1000	14500	140	5.512	1.39	0.934	0022-16

Impulse tested according to EN857 2SC for dash -10 and -16. Available with MSHA and Mega cover. In case of order use code THEYM2K and THEVM2K.