INTERPUMP Hypress FOUR SP

TSR04SP



APPLICATIONS :



APPLICABLE SPECIFICATIONS

IMM SPECS

4 high tensile spiral high flexibility. Performance according EN856 - ISO 3862 4SP.

Inner tube: Synthetic rubber, extruded whole without joints, of uniform thickness.
Reinforcement: 4 steel wire spirals.
Coverage: Anti-abrasive synthetic rubber, resistant to oils, fuels and atmospheric conditions.
Recommended fluids: Mineral and biological oils, glicol-water based, water, lubricants.
working temperature: from -40 to +100°C (intermittent 120°C), from -40 to +70° C for water based fluids, from 0 to +70°C water.

Product number	ID		Dimension	OD	Max WP		Min BP		Min BR		Weight (approx)		FERRULE
	mm	in	dash size		bar	psi	bar	psi	mm	inch	lb/ft	kg/m	TWO PIECES SKIVE
TSR04SP-06	9.5	3/8"	06	19.7	445	6453	1780	25810	180	7.087	0.448	0.667	0SI4-06
TSR04SP-08	12.7	1/2"	08	22.5	415	6018	1660	24070	230	9.055	0.522	0.777	0SI4-08
TSR04SP-10	16	5/8"	10	26.2	350	5075	1400	20300	250	9.843	0.635	0.945	0SI4-10
TSR04SP-12	19	3/4"	12	29.7	350	5075	1400	20300	300	11.811	0.764	1.136	0009-12
TSR04SP-16	25.4	1 "	16	36.7	280	4060	1120	16240	340	13.386	1.096	1.631	0009-16
TSR04SP-20	31.8	1.1/4"	20	44.6	210	3045	840	12180	460	18.11	1.440	2.143	004H-20
TSR04SP-24	38.1	1.1/2"	24	51.5	185	2683	740	10730	560	22.047	1.797	2.675	004H-24

Available with MSHA and Mega cover. In case of order use code TSRM4SP and TSRV4SP.