INTERPUMP Hyblast 15k

TFW0110 TFW0100



APPLICATIONS :



APPLICABLE SPECIFICATIONS

IMM SPEC. - ISO 7751

Safety factor 2,5:1. Light and compact. ISO 7751. Reliability and high performances.

Inner tube: Water resistant synthetic rubber.
Reinforcement: 4 steel wire spirals.
Coverage: Anti-abrasive syntetic rubber, resistant to oils, fuels and atmospheric conditions.
Recommended fluids: Water, water-soap based, glicol-water based.
working temperature: from -10 to +70°C, Max 100°C.

Product number	ID		Dimension	OD	Max WP		Min BP		Min BR		Weight (approx)		Ferrule	Coupling
	mm	in	dash size		bar	psi	bar	psi	mm	inch	kg/m	lb/ft		Series
TFW0110-04	6.4	1/4"	04	17	1100	15950	2750	39875	110	4.331	0.570	0.384	0019-04	M series
TFW0110-06	9.5	3/8"	06	20.7	1100	15950	2750	39875	140	5.512	0.890	0.599	00Y4-06	Y series
TFW0110-08	12.7	1/2"	08	24	1100	15950	2750	39875	180	7.087	1.150	0.774	00Y4-08	Y series
TFW0100-12	19	3/4"	12	31.6	1000	14500	2500	36250	240	9.449	1.800	1.211	00Y4-12	Y series

Marking: Available also embossed brand version. In case of order use code TFW0110N.

