INTERPUMP Hyblast 20k

TFW0145 TFW0135



APPLICATIONS :



APPLICABLE SPECIFICATIONS

IMM SPEC. - ISO 7751

Safety factor 2,5:1. Light and compact. ISO 7751. Reliability and high performances.

Inner tube: Water resistant synthetic rubber.
Reinforcement: 6 steel wire spirals.
Coverage: Anti-abrasive syntetic rubber, resistant to oils, fuels and atmospheric conditions.
Recommended fluids: Water, water-soap based, glicol-water based.
working temperature: from -10 to +70°C, Max 100°C.

Product number	ID		Dimension	OD	Max WP		Min BP		Min BR		Weight (approx)		Ferrule	Coupling
	mm	in	dash size		bar	psi	bar	psi	mm	inch	kg/m	lb/ft		Series
TFW0145-06	9.5	3/8"	06	23.3	1450	21025	3625	52563	180	7.087	1.350	0.909	00Y6-06	Y series
TFW0145-08	12.7	1/2"	08	27	1450	21025	3625	52563	220	8.661	1.800	1.211	00Y6-08	Y series
TFW0135-12	19	3/4"	12	35	1350	19575	3375	48938	260	10.236	2.670	1.797	00Y6-12	Y series

Marking: Available also embossed brand version. In case of order use code TFW0145N.