# INTERPUMP HyTruck 350 bar

## TTRK350

**APPLICATIONS :**





**APPLICABLE SPECIFICATIONS**

IMM Specs

NO-SKIVE hose. A line dedicated to tipper applications. Safety factor 2,5:1.

**Inner tube:** Synthetic rubber, extruded whole without joints, of uniform thickness oil and water resstant.
**Reinforcement:** 2 high tensile steel wire braids.
**Coverage:** Synthetic rubber resistant to oils, fuels and atmospheric conditions.
**Recommended fluids:** Mineral and biological oils, glicol-water based, water, lubricants.
**working temperature:** from -40 to +100°C (intermittent 125°), from -40 to +70° C for water based fluids, from 0 to +70°C water.

| Product number | ID | | Dimension | OD | Max WP | | Min BP | | Min BR | | Weight (approx) | | Ferrule |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | in | mm | dash size | | bar | psi | bar | psi | mm | inch | kg/m | lb/ft | |
| TTRK350-12 | 3/4" | 19 | 12 | 26 | 350 | 5075 | 875 | 12688 | 200 | 7.874 | 0.782 | 0.525 | 001C-12 |
| TTRK350-16 | 1" | 25.4 | 16 | 35.8 | 350 | 5075 | 875 | 12688 | 250 | 9.843 | 1.171 | 0.787 | 001C-16 |

**Marking:** Available only "mylar"