
INTERPUMP COMPRESSOR

TFDC011B

APPLICATIONS :





APPLICABLE SPECIFICATIONS

IMM - exceed EN 853 1SN

Pin pricked hose for compressor.

Inner tube: Synthetic rubber, extruded whole without joints, of uniform thickness.
Reinforcement: 1 steel wire braid.
Coverage: Anti-abrasive synthetic rubber, resistant to oils, fuels and atmospheric conditions.
Recommended fluids: Mineral oils, glycols and polyglycols, trasmission fluids, air, air with oil vapours, mineral oils in aqueous emulsion (up to +212°F/ + 100°C).
working temperature: from -40 to +135°C (intermittent 140°C).

Product number	ID		Dimension	OD	Max WP		Min BP		Min BR		Weight (approx)		Ferrule
	in	mm	dash size		psi	bar	bar	psi	mm	inch	kg/m	lb/ft	
TFDC011B04	1/4"	6.4	04	13.4	3263	225	900	13050	100	3.937	0.24	0.161	0001-04
TFDC011B05	5/16"	8	05	15	3118	215	850	12325	115	4.528	0.278	0.187	0001-05
TFDC011B06	3/8"	9.5	06	17.4	2610	180	720	10440	130	5.118	0.367	0.247	0001-06
TFDC011B08	1/2"	12.7	08	20.6	2320	160	640	9280	180	7.087	0.437	0.294	0001-08
TFDC011B10	5/8"	16	10	23.7	1885	130	520	7540	200	7.874	0.524	0.352	0001-10
TFDC011B12	3/4"	19	12	27.7	1523	105	420	6090	240	9.449	0.653	0.439	0001-12
TFDC011B16	1 "	25.4	16	35.6	1276	88	350	5075	300	11.811	1.001	0.673	0001-16
TFDC011B20	1.1/4"	31.8	20	43.5	914	63	250	3625	420	16.535	1.435	0.964	0001-20
TFDC011B24	1.1/2"	38.1	24	54.6	725	50	200	2900	500	19.685	1.711	1.15	0001-24
TFDC011B32	2 "	50.8	32	66.9	580	40	160	2320	630	24.803	2.357	1.584	0001-32

Compressed air applications require additional safety devices. Hoses are not designed and not approved for "air brake" applications.

Marking: Available only "embossed"